

PURITY C

Accessories / spare parts



BRITA FlowMeter 10 - 100	
Display unit (L/W/H)	62 / 62 / 22 mm
Sensor	80 / 50 / 26 mm
Flow range	10 - 100 l/h
Flow deviation	± max. 5%
Operating pressure	max. 8.6 bar
Pressure loss with flow of 100l/h	< 0,3 bar
Water intake temperature	4 - 30 °C
Cable length	max. 1.5 m
Inlet connection	G 3/8" Union nut
Outlet connection	G 3/8"
Order number	1033041

Calculates the residual capacity of the filter after the relevant filter capacity is set by recording the volumetric flow. Installed horizontally. With capacity indicator. FlowMeter is now equipped with a Velcro adhesive spot for comfortable fixation.



Service cartridge	
Dimensions (L/W/H)	125 x 125 x 233 mm
Max. filling volume cartridge cup	0.5 l
Operating pressure	0.5 - 8.6 bar
Water intake temperature	4 - 30 °C
Min. volume flow	2 l/m
Weight	350 g
Durability	2 years/max. 250 applications
Order number	1006579

Delivery without filter head.
The BRITA service cartridge is inserted temporarily in a PURITY C filter head in place of the filter cartridge in order to clean terminal devices. It is then filled with disinfected cleaning agents. The water which flows through the filter system flushes the cleaning agent directly into a connected terminal device. Fits in all PURITY C filter heads.



PURITY C wall mounting bracket	
Order number	1000480 (Pack 1)
Applicable for the sizes from C50 to C500.	



Wall mounting bracket	
Dimensions (L/W/H)	212,2 x 271,5 x 453,5 mm
Order number	1015502 (Pack 1)
Applicable for the sizes C500, C1100.	



PURITY C base	
Order number	1000494 (Pack 3)
Applicable for the sizes C50, C150, C300.	



Backflow preventer 3/8"	
Order number	1000639 (Pack 3)



Backflow preventer with securing clips JG 8*	
Order number	292069 (Pack 1)



Reducer sets	
Order number	1000898 (Pack 2)
3/4" external thread - 3/8" internal thread	



Securing clips for JG* connections	
Order number	536801 (Pack 50)



Gasket set I	
Order number	321800
<ul style="list-style-type: none"> • 3x flat gasket 3/4" • 2x flat gasket 3/8" • 2x O-rings (1" and 3/4" for inlet/outlet of filter head) 	

*Not available for Switzerland.

For more information please contact:

BRITA Water Filter Systems Ltd.

BRITA House | 9 Granville Way | Bicester | Oxfordshire OX26 4JT | Great Britain
 Tel.: +44 844 742 4990 | Fax: +44 186 936 5962
 clientservices@brita.co.uk | www.brita.co.uk

BRITA Water Filter Systems Distributors Pty Ltd

Suite 2, Level 9, 123 Epping Road | Macquarie Park, NSW, 2113 | Australia
 Tel.: +61 1300 955-021 | NZ: 0800 482-008
 professional@brita.com.au | www.brita.com.au

Headquarters: BRITA GmbH

Heinrich-Hertz-Strasse 4 | 65232 Taunusstein | Germany
 Tel.: +49 6128 746-0 | Fax: +49 6128 746-5033
 info@brita.net | www.brita.de